

DW275 EDUCATION PROJECTORS



Versatile Portable Projector with High Brightness



FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 4000 lumens of brightness and 20,000:1 contrast ratio for clear, crisp and bright presentations
- WXGA (1280 \times 800) native resolution scalable up to a maximum WUXGA (1920 \times 1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports









From meeting room to presentations anywhere on the road

The DW275 is a native WXGA digital projector from Vivitek. It features $\mathsf{DLP} \+ \! \mathbb{R}$ and $\mathsf{BrilliantColor}^{\text{\tiny{TM}}}$ technologies to display distinct, vibrant images in a widescreen format. The Vivitek DW275 features numerous connectivity options including two HDMI v1.4, a brightness level of 4000 Lumens and a 20,000:1 contrast ratio. With its light weight and compact form this is a short throw projector for easy installation that will fit any



DW275 SPECIFICATIONS

| Image | Display Type | Single chip DLP® Technology by Texas Instruments |
|--------------|---------------------------|--|
| | Brightness | 4000 ANSI Lumens |
| | Native Resolution | WXGA (1280 x 800) |
| | Max. Supported Resolution | WUXGA (1920 x1200) @60Hz |
| | Contrast Ratio | 20,000:1 |
| | Native Aspect Ratio | 16:10 |
| | Keystone Correction | Vertical: +/-40° |
| Optical | Throw Ratio | 1.55 - 1.86 : 1 |
| | Image Size (Diagonal) | 40" - 300" |
| | Projection Distance | 1.3m -10.2m |
| | Projection Lens | F = 2.42 - 2.62, f = 22.5 - 25.79 mm |
| | Zoom Ratio | 1.2x |
| | Offset | 1,04 |
| Features | Features | 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential) |
| Connectivity | I/O Connection Ports | VGA-In (15pin D-Sub) (x2), HDMI Number of Ports 1.4b (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service) |
| General | Lamp Life and Type | 5,500 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 210W |
| | Speakers | 2 W |
| | Dimensions (W x D x H) | 331 x 244 x 105 mm |
| | Weight | 2.6 kg |
| | Noise Level | 29dB Eco. Mode |
| | Power | Supply: AC 100-240V, 50/60Hz Consumption: 210W (Eco. Mode), 250W (Normal Mode), <0.5W (Standby) |
| | Warranty | Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whicheve comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first |
| | Standard Accessories | VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region Remote Controller (with battery), AC Power Cord |
| | Optional Accessories | Spare Lamp P/N (XX5810005600), Remote Control P/N (XX5040005400), Carrying Case P/N (XX3520000800) |